Specifications



C120N - circuit breaker - 3P - 125A - C curve

A9N18369

Main

Range	Acti9	
product name	Acti9 C120	
Product or component type	Miniature circuit-breaker	
Device short name	C120N	
Device application	Distribution	
Poles description	3P	
Number of protected poles	3	
[In] rated current	125 A at 30 °C	
Network type	AC	
Trip unit technology	Thermal-magnetic	
Curve code	С	
Breaking capacity	10000 A lcn at 230400 V AC 50/60 Hz conforming to EN/IEC 60898-1 6 kA lcu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA lcu at 220240 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA lcu at 380415 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA lcu at <= 375 V DC conforming to EN/IEC 60947-2	
Suitability for isolation	itability for isolation Yes conforming to IEC 60947-2	
Standards	EN/IEC 60947-2 EN/IEC 60898-1	
Product certifications	EAC	

Complementary

Network frequency	50/60 Hz	
[Ue] rated operational voltage	<= 375 V DC	
	380415 V AC 50/60 Hz	
	220240 V AC 50/60 Hz	
	440 V AC 50/60 Hz	
	230400 V AC 50/60 Hz	
Magnetic tripping limit	510 x ln	
[Ics] rated service breaking	7500 A 75 % conforming to EN/IEC 60898-1 - 230400 V AC 50/60 Hz	
capacity	4.5 kA 75 % conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz	
	7.5 kA 75 % conforming to EN/IEC 60947-2 - 380415 V AC 50/60 Hz	
	15 kA 75 % conforming to EN/IEC 60947-2 - 220240 V AC 50/60 Hz	
	10 kA 100 % conforming to EN/IEC 60947-2 - <= 375 V DC	
Limitation class	3 conforming to EN/IEC 60947-2	
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60947-2	
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-2	

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

Contact position indicator	Yes	
control type	Toggle	
local signalling	ON/OFF indication	
Mounting mode	Clip-on	
Mounting support	35 mm symmetrical DIN rail	
Comb busbar and distribution block compatibility	YES	
9 mm pitches	9	
Height	81 mm	
Depth	73 mm	
Width	81 mm	
Net weight	0.615 kg	
Colour	White	
Mechanical durability	20000 cycles	
Electrical durability	5000 cycles conforming to IEC 60947-2	
Locking options description	Handle sealable with cable diameter 0.7mm in OFF or ON position	
Connections - terminals	Tunnel type terminals150 mm² rigid Tunnel type terminals1.535 mm² flexible	
Wire stripping length	15 mm	
Tightening torque	3.5 N.m	
Earth-leakage protection	Separate block	

Environment

IP degree of protection	IP20 conforming to IEC 60529	
Pollution degree	3 conforming to IEC 60947-2	
Overvoltage category	IV	
Tropicalisation	2 conforming to IEC 60068-1	
Relative humidity	95 % at 55 °C	
Operating altitude	2000 m	
ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	8.000 cm
Package 1 Length	8.000 cm
Package 1 Weight	583.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	8.500 cm

Package 2 Width	9.500 cm
Package 2 Length	33.000 cm
Package 2 Weight	2.403 kg
Unit Type of Package 3	S03
Number of Units in Package 3	24
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	14.731 kg

Contractual warranty

Warranty

18 months

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

ą	Environmental footprint	
	Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	71
	Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Ab76a2c8-39ad-4485-a07c-19f81f42d0a0
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds

Use Again

igcelow Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins