

Illuminated push button, Harmony XB4, metal, green flush, 22mm, universal LED, plain lens, 1NO + 1NC, 24V AC DC

Local distributor code:

23706459

XB4BW33B5

Important message: A change in appearance may be noted on the product but does not affect its use in terms of function and safety. This makes it compatible with our Universal LED blocks.

EAN Code: 3389110892048

Main

Range of product	Harmony XB4					
Product or component type	Illuminated push-button					
Device short name	XB4					
Bezel material	Chromium plated metal					
Fixing collar material	Zamak					
Mounting diameter	22.5 mm					
Sale per indivisible quantity	1					
Head type	Standard					
Shape of signaling unit head	Round					
Type of operator	spring return					
Operator profile	Green flush					
Operator additional information	With plain lens					
Contacts type and composition	1 NO + 1 NC					
Contact operation	Slow-break					
Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to IEC 60947-1 Screw clamp terminals, 1 x 0.222 x 2.5 mm² without cable end conforming to IEC 60947-1					
Light source	Universal LED					
Bulb base	Integral LED					
[Us] rated supply voltage	24 V AC/DC at 50/60 Hz					

Complementary

Height	47 mm		
Width	30 mm		
Depth	57 mm		
Terminals description ISO n°1	(21-22)NC (13-14)NO		
Net weight	0.097 kg		
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m		
Contacts usage	Standard contacts		

Positive opening	With conforming to IEC 60947-5-1 appendix K			
Operating travel	1.5 mm (NC changing electrical state)2.6 mm (NO changing electrical state)4.3 mm (total travel)			
Operating force	3.5 N NC changing electrical state 3.8 N			
Mechanical durability	10000000 cycles			
Tightening torque	0.81.2 N.m conforming to IEC 60947-1			
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver			
Contacts material	Silver alloy (Ag/Ni)			
Short-circuit protection	10 A cartridge fuse type gG conforming to IEC 60947-5-1			
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1			
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1			
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1			
[le] rated operational current	3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1			
Electrical durability	1000000 cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C			
Electrical reliability	Λ < 10exp(-6) at 5 V and 1 mA in clean environment conforming to IEC 60947-5-4 Λ < 10exp(-8) at 17 V and 5 mA in clean environment conforming to IEC 60947-5-4			
Signalling type	Steady			
Current consumption	18 mA			
Service life	100000 h at rated voltage and 25 °C			
Surge withstand	1 kV conforming to IEC 61000-4-5			
Supply voltage limits	19.230 V DC 21.626.4 V AC			
Device presentation	Complete product			
Environment				
Protective treatment	тн			
Ambient air temperature for storage	-4070 °C			
Ambient air temperature for operation	-4070 °C			
Electrical shock protection class	Class I conforming to IEC 60536			
IP degree of protection	IP66 conforming to IEC 60529 IP67 IP69 IP69K			

NEMA degree of protection	NEMA 13			
	NEMA 4X			
K degree of protection	IK06 conforming to IEC 50102			
Standards	IEC 60947-5-1			
	JIS C8201-5-1			
	IEC 60947-5-5			
	CSA C22.2 No 14			
	IEC 60947-5-4			
	IEC 60947-1			
	UL 508			
	JIS C8201-1			
Product certifications	CSA			
	LROS (Lloyds register of shipping)			
	BV			
	UL listed			
	DNV			
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6			
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC			
	60068-2-27			
	50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC			
	60068-2-27			
Resistance to fast transients	2 kV conforming to IEC 61000-4-4			
Resistance to electromagnetic ïelds	10 V/m conforming to IEC 61000-4-3			
Resistance to electrostatic	6 kV on contact (on metal parts) conforming to IEC 61000-4-2			
discharge	8 kV in free air (in insulating parts) conforming to IEC 61000-4-2			
Electromagnetic emission	Class B conforming to IEC 55011			

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	5.500 cm
Package 1 Length	8.500 cm
Package 1 Weight	96.600 g
Unit Type of Package 2	S03
Number of Units in Package 2	150
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	14.919 kg
Unit Type of Package 3	P06
Number of Units in Package 3	1200
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	127.352 kg

Logistical informations

Country of origin FR

Contractual warranty

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Total lifecycle Carbon footprint	14
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	425812e5-011f-4fb4-ad1b-fc9cf9865300
REACh Regulation	REACh Declaration


Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

XB4BW33B5

Dimensions Drawings

Dimensions



- \boldsymbol{e} : clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.
- (1) Additional row of contacts or double contact


XB4BW33B5


Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board

Connection by Faston Connectors







- (1) Diameter on finished panel or support
- (2) 40 mm min. / 1.57 in. min.
- (3) 30 mm min. / 1.18 in. min.
- (4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm $_0^{+0.4}$ / 0.88 in. $_0^{+0.016}$)
- (5) 45 mm min. / 1.78 in. min.
- (6) 32 mm min. / 1.26 in. min.

Technical Illustration

Dimensions







-		a (mm)	a (m.)	p (mm)	D (17.)
Z8E****	ZBV••••	40	1.57	30	1.18
Z8E3	3 ZBV••••3	45	1.77	32	1.26
Z8E******	ZBV•••••	40	1.57	30	1.18
ZBE5 ZBV	2	50	1.97	30	1.18
Z8E****9	ZBV••••9	40	1.57	30	1.18
ZBRT•	ZBRV1	40	1.57	30	1.18

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB4



Image of product / Alternate images

Alternative









